

## 40X40X10 mm

## KF0410-01 Series



- **Frame** : Plastic Material UL 94V-0
- **Impeller** : Plastic Material UL 94V-0
- **Speed Range** : ±10%

### SPECIFICATIONS

Model	Bearing	Rated Voltage (V)	Operating Voltage (V)	Air Flow (CFM)	Static Pressure (inchH <sub>2</sub> O)	Speed (R.P.M.)	Input Current (Amp)	Input Power (Watt)	Nominal Power (Watt)	Noise (dBA)	Weight (g)
KF0410B5H-AO	B	5	4.25~5.75	7.55	0.183	7500	0.16	0.80	0.8	33.7	16
KF0410B5H				6.00	0.128	6000	0.13	0.65	0.8	28.0	
KF0410B5M				5.38	0.106	5400	0.09	0.45	0.5	25.7	
KF0410B5L				4.12	0.066	4200	0.07	0.35	0.4	20.9	
KF0410S5H	S			6.00	0.128	6000	0.20	1.00	1.2	28.0	
KF0410S5M				5.38	0.106	5400	0.10	0.50	0.8	25.7	
KF0410S5L				4.12	0.066	4200	0.08	0.40	0.6	20.9	
KF0410B1H-AO				B	12	10.2~13.8	7.55	0.183	7500	0.066	
KF0410B1H	6.00	0.128	6000				0.066	0.80	0.8	28.0	
KF0410B1M	5.38	0.106	5400				0.058	0.70	0.7	25.7	
KF0410B1L	4.12	0.066	4200				0.05	0.60	0.6	20.9	
KF0410S1H	S	6.00	0.128	6000			0.08	0.96	1.2	28.0	
KF0410S1M		5.38	0.106	5400			0.066	0.80	0.8	25.7	
KF0410S1L		4.12	0.066	4200			0.058	0.70	0.7	20.9	
KF0410B2S-AI		B	24	20.4~27.6			7.55	0.183	7500	0.058	
KF0410B2S	6.58				0.148	6600	0.058	1.40	1.4	30.6	
KF0410B2H	6.00				0.128	6000	0.05	1.20	1.2	28.0	
KF0410B2M	5.38				0.106	5400	0.04	0.96	1.0	25.7	
KF0410B2L	4.12				0.066	4200	0.03	0.72	0.8	20.9	
KF0410S2H	S				6.00	0.128	6000	0.05	1.20	1.2	28.0
KF0410S2M					5.38	0.106	5400	0.04	0.96	1.0	25.7
KF0410S2L					4.12	0.066	4200	0.03	0.72	0.8	20.9

Specifications subject to change without notice

The 7<sup>th</sup> character of Model No means the bearing code. Please refer to the page "PART NUMBER SYSTEM".

Please contact us for detail if your request bearing system is not shown in the above list.

