



HSF

NOTES:

Rated Current:2.0AMP.
 Contact Resistance:20mΩ Max.
 Withstand Voltage:500V AC/DC
 Insulation Resistance:1000MΩ Min.
 Operation Temperature:-40°C to +105°C

Contact Material:Brass
 Contact Plating:Au or Sn Over Ni
 Insulator Material:LCP+30%G.F UL94V-0 BK



Recommended P.C.B Layout (Top Side)
 (PCB BOARD TOLERANCE±0.05)



Ordering Information

1220-25 XX XX S 190 D 0 XX ▲▲

No.of Pins Per Row:02~40	Contact Plating G0=Gold Flash G3=10u"Gold G4=15u"Gold G5=30u"Gold S0=Gold Flash/Tin S3=10u"Gold/Tin S4=15u"Gold/Tin S5=30u"Gold/Tin SN=Tin SM=Matte Tin	Pin Length L=19.0mm	Insulator Material D=LCP	Packing 0=PE Bag 1~99	Series No.
-----------------------------	---	------------------------	--------------------------------	-----------------------------	------------



				OPERATION	DRAW	DATE	SCALE	Fit	PART NO.
				x.X ±0.40	Liu	2018/01/19	UNIT	mm	1220-25XXXXX190D0XX ▲▲
A1	2018/01/19	Modify P/N	▲▲	x.XX ±0.25	CHECK	DATE	SIZE	A4	TITLE:
A0	2015/07/23	NEW	-----	x.XXX ±0.15	APPROVE	DATE	SHEET	1/1	PH2.00 FIVE ROW DOUBLE PLASTIC 180° H=2.5
REV	DATE	MODIFICATION DESCRIPTION	CHANGE	Angle ± 3'			PROJ.	☉	Customer NO.
				DIM TOL					